

# *Product Overview:* **HYDROXSEAL MOLD REMOVER**

## Description:

HYDROXSEAL MOLD REMOVER is a potent agent safeguarding against mold, algae, and harmful microorganisms. Designed for swift and effective removal, it works on various surfaces, including concrete, dispersion paints, wood, plastics, and more.

## Key Features:

- **Antimicrobial Components:** Registered and approved for antimicrobial production.
- **Ecological:** Non-toxic, environmentally friendly formula.
- **Fast Action:** Rapid and effective on treated surfaces.

## Usage Information:

### Consumption:

- 500ml per 5m<sup>2</sup>, depending on surface purpose and roughness.

### Storage:

- +5 to +35°C in original packaging, not recommended for prolonged sun exposure, and must not freeze.

### Duration:

- 12 months.

### Packaging:

- Available in 250ml, 500ml, 1l, 5l, 10l plastic containers.

## Application:

- Applied directly to contaminated surfaces, left for 20 minutes, and wiped off with a cloth.
- No pre-rinsing required; repeat on multiple infected surfaces.

## Safety Instructions:

- **Protection:** Use protective gloves to avoid skin contact.
- **Skin Contact:** Wash contaminated skin immediately with soap and water.
- **Eye Contact:** Rinse eyes immediately with a large amount of water; seek medical help.

## Environmental Considerations:

- Dispose of used packaging according to local waste regulations.

## Safety Instructions:

### Protective Measures:

- Use gloves to avoid skin contact.

### Skin Contact:

- Wash affected areas with soap and water.

### Eye Contact:

- Rinse eyes with water; seek medical help if needed.

## Recommendations:

- Adapt application method and quantities to facility conditions.
- Use appropriate equipment based on recommendations.